

ME910C1 Mini PCIe Series

LTE Cat M1/NB1



Product Description

The ME910C1 series mini PCIe (mPCIe) modules are optimized for LTE-M and NB-IoT networks and are available with 2G fallback options. The ME910C1 series modules are interchangeable with other modules in the xE910 mPCIe family.

Key Benefits

- Standard mini PCIe data card form factor
- Best-in-class 3GPP Rel. 13 platform
- Easy to integrate with peripherals and actuators using USB 2.0 HS, UART and user-definable GPIOs
- Battery-friendly 1.8 V GPIO
- Internet friendly with integrated TCP/IP and UDP/IP stacks
- Simple drop-in migration and technology design reuse path to 2G and 3G with any xE910 module
- Firmware Over-the-Air (FOTA) update
- Benefit from Rel. 13 features for LTE-M and NB-IoT, such as Power Saving Mode (PSM), extended Discontinuous Reception (eDRX), enhanced coverage, higher LTE-M and NB-IoT data rates

Family Concept

Longevity and cost-efficiency are built into the developer's product architecture with the Telit Cinterion on family "design once, use anywhere" philosophy. Designers looking to add LTE capabilities to commercial and industrial computing devices benefit from the simple yet powerful mPCIe form factor with the flexibility to choose another technology best suited for the application environment from any one of the other models in the xE910 mPCIe series.

OneEdge™ Features

Telit Cinterion offers ME910C1 mini PCIe with OneEdge, a software suite integrated with deployment and management tools to address the complexity expected with the exponential growth in the number of IoT devices. The following key components are included:

- **Lightweight M2M protocol** enables comprehensive device management, FOTA updates and application enablement of low-power devices with the goal of more robust and secure connections.
- **Telit IoT AppZone** can run code and applications directly inside the Telit Cinterion module.
- **Location services** provide the position of devices even in the absence of a GNSS connection.

Variants

Cat M1/NB1 with 2G fallback for worldwide deployments

AVAILABLE FOR

Worldwide



ONEEDGE™

ME910C1 Mini PCIe Series

ME910C1-WW

Market	Worldwide
4G Bands (MHz)	B1 (2100), B2 (1900), B3 (1800), B4 (AWS 1700), B5 (850), B8 (900), B12 (700), B13 (700), B18 (800), B19 (800), B20 (800), B26 (850), B28 (700)
2G Bands (MHz)	B2 (1900) B3 (1800) B5 (850) B8 (900)
Approvals	PTCRB, GCF, RED, FCC/IC, RCM, Jate, Telec, CCC, AT&T, Verizon, NTT DoCoMo, Deutsche Telekom, Anatel, Telstra, Ifetel, Rogers, Telus, US Cellular

Product Features

- LTE UE Cat M1/NB1
- 3GPP Rel. 13 compliant
- Half-duplex FDD
- Single Rx, single antenna
- 3GPP Rel. 12 PSM
- 3GPP Rel. 13 eDRX
- 3GPP Rel. 13 extended coverage
- Control via AT commands according to 3GPP TS 27.005, 27.007 and customized AT commands.
- SIM application tool kit 3GPP TS 51 01
- SMS
- IPv4/IPv6 stack with TCP and UDP protocol
- OMA Lightweight M2M (LwM2M)
- FOTA update
- Telit Cinterion application development environment: AppZone C
- SSL
- Optional embedded GNSS (GPS, GLONASS, Beidou, Galileo)

Hardware and Electrical Specifications

- Dimensions: 51 x 30 x 3.2 mm
- 181-pin LGA interface
- 10 I/O ports (1.8V) including multifunctional I/Os
- USB 2.0 HS
- UART
- SPI
- 1.8 V/3 V SIM interface
- Temperature Range: -40 °C to +85 °C
- Supply voltage
 - Nominal: 3.3 V dc
 - Range: 3.0-3.6 V dc
- REACH and RoHS compliant
- RED (Rurope)

Data

- LTE Cat M1**
 - Uplink up to 375 kbps
 - Downlink up to 300 kbps
- LTE Cat NB1**
 - Uplink up to 62.5 kbps
 - Downlink up to 21 kbps
- EGPRS**
 - Uplink up to 236 kbps
 - Downlink up to 296 kbps

QUESTIONS? VISIT WWW.TELIT.COM/CONTACT-US

 Like Us on Facebook
  Follow Us on LinkedIn
  Follow Us on X
  Subscribe to Our Channel